



EXTENDING YOUR REACH

Change Region

Language
English

Search

- [Home](#)
- [Products](#)
- [Used Equipment](#)
- [Industries](#)
- [Financial Solutions](#)
- [Services & Parts](#)
- [Military & Government](#)
- [Career Center](#)
- [Safety](#)
- [About JLG](#)
- [Distributor Locator](#)
- [My JLG](#)
- [Contact Us](#)

Aerial Work Platforms / Boom Lifts » Electric Scissor Lifts » ES Series Scissor Lift » 2630ES

2630ES Specifications

Performance Data	
Drive Speed, Lowered	2.75 mph / 4.43 kmph
Drive Speed, Elevated	0.5 mph / 0.8 kmph
Gradeability	25%
Turning Radius - Inside	Zero
Turning Radius - Outside	81" / 2.06 m
Tire Size	16 x 5" / 406 x 125 mm
Tire Type	Non-Marking Solid
Brakes (on drive wheels)	Electric, Friction

Dimensions	
Platform Height - Elevated	25' 6" / 7.77 m
Platform Height - Lowered	48.5" / 1.23 m
Platform Railing Height	43.3" / 1.10 m
Overall Height	7' 7.8" / 2.33 m
Overall Height - With Rails Folded	6' 4.5" / 1.94 m
Platform Dimensions	30 x 90.5" / 0.76 x 2.3 m
Platform Dimensions - Platform Extension	35.5" / 90 cm
Overall Length	7' 6.5" / 2.3 m
Overall Width	30" / 76 cm
Wheelbase	6' 2" / 1.88 m
Ground Clearance	3.5" / 89 mm
Platform Capacity	500/800 lb / 227/363 kg
Platform Capacity - Capacity on Extension	250 lb / 113 kg
Rail Type	Fold Down
Lift/Lower Time	40/40 seconds
Maximum Drive Height	25' 6" / 7.77 m
Weight* (ANSI/CSA)	4,750 lb / 2,155 kg
Ground Bearing Pressure	90 psi / 6.32 kg/cm ²

Power System/Chassis	
Batteries	4 x6V, 220 amp-hr
Charger	20 Amp Automatic / 120V/240V - 50/60 Hz
Drive	24V Electric / 8 hp
Pump	Fixed Displacement Gear
Hydraulic Reservoir	1.25 gal. / 4.73 L

- Available Options
- 1000 Watt - AC Inverter/Charger
 - Flashing Amber Beacon
 - Spring-Loaded Gate
 - 245 Amp-Hour Batteries
 - AGM Batteries
 - Lifting Lugs

[Specifications](#)
[Accessories](#)

Downloads

- [Brochure](#)
- [ES Series Spec Sheet.pdf](#)



[Print](#)

- **UL® EE Rating**
- **Platform Padding**
- **Platform Padding with Proximity Switches**
- **1/2" Air Line to Platform**
- **Nite Bright**

* Certain weights and dimensions may vary due to options and to compliance with country standards.